

"OPTICAL CABLE CORPORATION (OCC) RESERVES THE RIGHT TO REVISE ANY AND ALL DESIGN SPECIFICATIONS."

SPECIFICATIONS

MATERIALS:

- HIGH-IMPACT PVC RATED 94V-0

FEATURES:

- SUPPORTS (4) KMJ STYLE JACKS OR INSERTS.
- ACCOMMODATES UP TO .350" CABLE O.D.
- PROVIDED WITH (2) #6-20 X 3/4" MOUNTING SCREWS AND DOUBLE-SIDED TAPE.

CODE & COMPLIANCE:

- UL LISTED
- CSA CERTIFIED
- RoHS COMPLIANT

UNCONTROLLED COPY

SMEK412	SURFACE MOUNT ENCL, 4 PORT, KMJ, BRIGHT WHITE
SMEK402	SURFACE MOUNT ENCL, 4 PORT, KMJ, BLACK
SMEK401	SURFACE MOUNT ENCL, 4 PORT, KMJ, OFFICE WHITE
SMEK400	SURFACE MOUNT ENCL, 4 PORT, KMJ, ELEC. IVORY
OCC PART NO.	DESCRIPTION

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES.
 TOLERANCES: FRACTIONS ±1/32"
 ANGLES ±1/2°
 3 PLACE DECIMALS ±.005"
 2 PLACE DECIMALS ±.01"

MATERIAL
RIGID PVC

FINISH
SEE NOTES


CHECKED	R.B.SMITH	DATE	8/26/05
ENGINEER	J.YANIK	DATE	2/4/05
APPROVED	J.CALLOWAY	DATE	5/9/14
PREVIOUS DWG			
NEXT DWG			



33 Superior Way
Swannanoa, NC 28778
Phone: 828-298-2260
Fax: 828-298-2487
www.occfiber.com

DWG TITLE
CUSTOMER DRAWING, 4 PORT, KMJ, SURFACE MOUNT ENCLOSURE

SIZE	C	DWG NO.	C107173	REV	F
SCALE:	NONE	SHEET	1 OF 1		



FILENAME	C107173F.DFT	SCALE:	NONE	SHEET	1 OF 1
----------	--------------	--------	------	-------	--------