

THE ADVANCED LIGHTWEIGHT REEL STAND (ALRS)

OCC ADDS ANOTHER INNOVATIVE PRODUCT TO OUR LINE OF TOUGH, DEPLOYABLE REEL ACCESSORIES.



OCC'S ALRS series of Lightweight Reel Stands represent a significant advancement in cable deployment and retrieval technology. The ALRS is a highly portable, folding A-frame stand used for paying out and retrieving cable (both copper and fiber optic) in a harsh environment. Designed for quick and easy deployment and operation, the ALRS requires no tools for set up, and when configured for transport, all pieces are maintained within the unit.

Engineered for the military, ready for you. The OCC ALRS reel stand came from a direct collaboration with the U.S. Military. Their inputs helped develop a highly portable folding A-frame stand that

Features & Benefits:

> Provides more functionality than the existing RL-31 reel stands at one third of the weight

> Constructed of lightweight aluminum, with stainless steel hardware, the stand is ozone, fungus and corrosion resistant

> Conforms to Army Performance Specification A3354296

> Designed for rugged environments from rain forests to rugged mountains, from hot and humid to freezing cold, from deserts to coastal conditions

- > Available with either 1" square or 1" round axle.
- > Bi-directional operation without tipping over

is designed for quick and easy deployment and operation – built to withstand the rigors of daily use.

OCC's ALRS with its lightweight aluminum construction weighs a third of the traditional RL-31 reel stand and offers more functionality. This simple to operate stand requires no tools for assembly, can operate from either direction without tipping and is available with solid or split axles for independent rotation.

Smart, rugged construction. All the pieces of the ALRS attach to the unit, making assembly a snap. Designed for rugged environments in all temperature ranges, the ALRS is ozone, fungus, and corrosion resistant.

> Compatible with most common military cable reels DR-5, DR-7, DR-8, RFO-100 through RFO-1000, and CECOM A336463 compliant reels such as the OCC MARS[™] reels, AFO-100 through AFO-1000)

> Available with solid axles or split axles which allow independent rotation

- > No tools required for assembly or disassembly
- > Optional storage pouch for ground stakes and/or toe clamps (also optional) or other accessories

> Fully supported in the DOD logistics system with National Stock Numbers (NSN) for both complete ALRS assemblies and spare/replacement parts



Performance Specifications

PARAMETER	SPECIFICATION	PERFORMANCE			
Protective Finish	A3354296	CARC or Powdercoat			
Color Options	A3354296	Olive drab, desert tan, or black			
Weight	A3354296	Approx. 22 lbs.			
Configuration Options	A3354296	Ground mobile fixed (A-frame), rolling (wheel barrow), and litter carry (flat extended)			
Rain	A3354296	10cm/hr min.			
Moisture Resistance	A3354296	79°F and 95°F with RH between 79% and 95%			
Salt Fog	MIL-STD-810G	Method 509.5 Salt Fog			
High Temperature	A3354296	Operational: 126°F; Storage: 160°F			
Low Temperature	A3354296	Operational: -26°F; Storage: -31°F			
Vibration and Bounce	MIL-STD-810G	Method 514.6, Paragraph 4			
Maximum Cable Reel Weight	n/a	140 lbs. / 63 kg			
Dimensions	39"w (including cranks) x 27"h x 32"d (legs expanded)				







Ordering Information

Ree	l Stand Family – ALRS	-1	Α	PG	1	S	1	C
AXLI 1 2 3 4	TYPE Single axle, 1" square Split axle, 1" square Split and single axle, 1" square (both provid Single axle 1" round	led)						BASE CLAMPNNONECTOE CLAMPS (4 EACH)SSTAKES (6 EACH)ETOE CLAMPS (4) & STAKES (6)
MAT A	ERIAL ALUMINUM						POU 0 1 2	ICH* NONE ONE TWO
COA PG PT PB	FING Olive drab powder coating Desert tan powder coating Black powder coating					CRAN S D	IK Singl Dual	e
MG MT MB	Military carc green coating Military carc tan coating Military carc black coating				BRAI 0 1 2	KE None One Two		

Army standard unit NSN:

NSN 8130-01-630-1702 (Part no. ALRS2AMG2D1C, CARC Green) NSN 8130-01-630-1792 (Part no. ALRS2AMT2D1C, CARC Tan)

OCC ROANOKE, VA

Corporate Headquarters and Fiber Optic Cable Manufacturing Facility 5290 Concourse Drive Roanoke, VA 24019 USA 540.265.0690 or 800.622.7711

OCC DALLAS, TX

Harsh Environment and Specialty Connectivity Manufacturing Facility 1700 Capital Avenue, Suite 150 Plano, TX 75074 USA 972.509.1500 or 877.509.1500

OCC ASHEVILLE, NC

*Any specific fabric pattern options, must be specified at time of quote/purchase.

Enterprise Connectivity Manufacturing Facility 33 Superior Way Swannanoa, NC 28778 USA 828.298.2260 or 800.880.7674

VISIT US AT OCCFIBER.COM